⑫ EUROPEAN PATENT SPECIFICATION

�civ Method and apparatus for merge processing in a text processing system.

㊎ Proprietor: **International Business Machines
Corporation
Old Orchard Road
Armonk, N.Y. 10504 (US)**

㊔ Inventor: **Levine, Lewis Jay
7609 Valburn Drive
Austin Texas 78731 (US)**
Inventor: **Shipp, Kenneth Osborn, Jr.
1108 Gemini Drive
Austin Texas 78758 (US)**

㊙ Representative: **Tubiana, Max
Compagnie IBM France Département de
Propriété Industrielle
F-06610 La Gaude (FR)**

EP 0 075 732 B1

BEST AVAILABLE COPY

Description

Technical field of the invention

This invention relates to a text processing system and more particularly to means and methods for
5   enabling an operator to merge various keyed entries of text data to create a document on a text processing
system.

Description of the background art

It is known in the prior art to merge keyed text data to produce a document utilizing stop codes. In a
10 typical application, known as repetitive letters, the operator creates multiple versions of the same
document, differing only in variable replacement text included in that document. The repetitive letter is
created by keying and storing the master repetitive letter or shell document. The shell document is created
in a similar manner to any other letter except that instead of typing the information that will change from
letter to letter (for example, the name, adress, and salutation), a Switch Code is typed at each point in the
15 shell document where the information that changes will appear. The parts of the letter that change are
called variable information or variables, and the Switch Codes enable the operator to locate the places in
the letter where the variables are typed.

Pagination functions typically process variable length input lines of text into uniform pages of equal
length lines, keep related text on a single page, allow text lines from other documents to be inserted, and
20 make hyphenation decisions or assist an operator of the text processing system in making hyphenation
decisions when a word crosses a line ending boundary. The pagination functions are based on the concept
of paginating a text document entered by an operator to produce an attractive appearing letter, for
example, with equal length lines, etc. An extension of pagination, offered by some text processing systems,
allows variable data from a data processing-like file to be merged with a text document to generate a
25 composite document, for example, personalized letters. This capability is generally referred to as "merge
file/text" or "auto letters". In this system, the variable data is identified by a "set symbol".

There has developed in the text processing market a requirement for systems providing enhanced
operator productivity without requiring programming skills on the part of the text processing system
operator.

30 IBM Technical Disclosure Bulletin, Vol. 21, No 11, April 1979 pp. 4323-29 discloses a system providing
means for processing pre-defined forms making use of a CRT display that provides an inter active rapport
between the operator and the system.

GB—A—1363910 relates to data processing means arranged for processing text in which symbolic
variables are used in a text stream and are processed by a text composition program. More particularly the
35 invention relates to the use of a variable symbol for items of an ordered sequence which are used in the text
stream.

The problem still to be solved arises from the fact that existing word processing systems are not
providing convenient interactive text processing means enabling the operator to merge prestored texts in a
selective way.

40 In accordance with the present invention, an interactive text processing system as defined in claim 1
and a method of operating an interactive text processing system as defined in claim 4 are provided in which
the operator interface is usable by an operator with no programming skills.

In a specific embodiment, the operator has the option of choosing a merge operation in response to
Switch Codes or a merge operation in response to Named Variables.

45

Brief description of the drawings

Fig. 1 is a block diagram of the system embodying the present invention;

Fig. 2 is a block diagram of the processor shown in Fig. 1;

Fig. 3 illustrates the Merge Tasks Menu as it would appear on the display device of Fig. 1 in accordance
50 with the present invention;

Fig. 4 illustrates the Merge with Named Variables Setup Menu as it would appear on the display device
of Fig. 1 in accordance with the present invention;

Fig. 5 illustrates the Merge with Switch Codes Setup Menu as it would appear on the display device of
Fig. 1 in accordance with the present invention;

55 Fig. 6 is a hierarchy diagram of the merge subsystem control routines in accordance with the present
invention.

Description of the preferred embodiment

Referring now to Fig. 1, a portion of the text processing system is shown, including a processor 10 to
60 which is connected a bus 12 leading from a keyboard 14. Character data generated by manual actuation of
keyboard 14 applies character-related signals to processor 10 which provides on an output memory bus 16
a data stream in which the characters selected by actuation of keyboard 14 appear suitably encoded.

Keyboard 14 comprises a normal set of graphic symbol keys such as letters, numbers, punctuation
marks, and special character keys, plus text format or control keys like carriage return, indent, etc. In
65 addition, the keyboard includes a second set of control keys for issuing special control commands to the

system. The control keys include cursor movement keys, keys for setting the keyboard into a number of different modes, etc.

Memory bus 16 extends to a memory unit 20, to a display unit 22, to a diskette unit 24 and to a printer 25.

5   Memory 20 includes text storage buffers 26, 26' which serve to store the coded data stream comprising the text input initially entered through the keyboard 14. Included in the text storage buffers 26, 26' are storage sections for the identity of the active document format which contains the active document keyboard character set (KB/CS) namely, in portions 28, 28'.

Text storage buffer control blocks 30, 30' are linked to buffers 26, 26' and include a cursor control
10 section 32, 32'. The text storage buffers 26, 26' are linked to the data on the diskette 24 by storage access control blocks (SACB) (not shown), one of which is included for each text storage buffer.

A text storage buffer manager 34 is linked by channels 36, 36' to the control blocks 30, 30' by channels 38, 38' to the buffers 26, 26' and by channels 40 and 42 to a merge controller 44.

Merge controller 44 provides the control routines necessary to execute a merge operation in
15 conjunction with text data stored in the Output TSB 26, the Fill-In TSB 26' and the record buffer 27 as will be described in greater detail later in this specification.

A keystroke control routine block 46 is provided to select the appropriate routine for the entered keystroke and is connected to Merge controller 44 by channel 47. The control blocks 30, 30' are connected to merge controller 44 by channels 48, 48'. Buffer 26 is coupled by channel 50 to a display access method
20 block 52 which is coupled by way of channel 54 to a display refresh buffer 56. A display control block 58 is coupled by channel 60 to the display access method block 52. Get control block 57 functions to fetch data which is stored in record buffer 27.

In accordance with the present invention, a channel 62 is connected from the active document format storage 28 of buffer 26 to the merge controller 44. Further, an input keyboard character set (KB/CS) block 64
25 stores the identity of any desired input keyboard character set of keyboard 14 and is connected by way of channel 66 to the merge controller 44.

The display access method block has corresponding access method blocks for the diskette 24 and the printer 25. Each of the blocks serves as an interface to the corresponding unit.

The display refresh buffer 56 contains the actual text which is shown on display 22 while the buffer 26
30 contains all of the display text plus control data.

Menu manager 29 selects the appropriate menu to be displayed on display 22 and stores the menu image in menu buffer 31. At the appropriate time, the menu image is transferred by channel 50 to the display access method block 52 for routing to the display refresh buffer 56.

In operation of the system of Fig. 1, the encoded data stream on memory bus 16 is stored in the text
35 storage buffer 26. In the process of correction and editing the contents of the text storage buffer 26, selected portions or lines of a page are presented on display unit 22. Stored in active document format section 28 is the code designating the keyboard character set that was employed in the production of the coded data stream appearing on memory bus 16 leading from processor 10 and applied from text storage buffer 26 to display unit 22 for edit.
40 If it is necessary, for example, to insert a graphic item into the text displayed on unit 22, then a cursor, conventionally available on such display systems, is placed below the character on display 22 at the location immediately preceding which an insert is to be made. The input keyboard character set identification of which the graphic item to be inserted forms a part, is applied by way of channel 66 to the merge controller 44.
45 Referring to Fig. 2, the processor 10 is further detailed to show typical logic hardware elements as found in such processors. The processor may be a commercially available unit, such as from Intel Corporation and identified by the number 8086, or any of the recognized functionally equivalent, currently available microprocessors. Typically, the processor includes a control logic unit 70 which responds to interrupts on a device bus 71 from the keyboard 14. The control logic unit 70 is also connected to a data and
50 address bus 82 interconnected to various other logic units of the processor 10.

In response to a fetch instruction from the random access memory 20, the control logic unit 70 generates control signals to other logic elements of the processor. These control signals are interconnected to the various elements by means of a control line 72 which is illustrated directly connected to an arithmetic logic unit 73 and identified as a "control" line 72 to other elements of the processor. Sequence operation of
55 a control unit 70 with other logic elements of the processor 10 is achieved by means of clock pulses input to the processor from an external clock source on a clock line 74. Line 74 is also shown interconnected to other logic elements of the processor 10 detailed in Fig. 2.

Data and instructions to be processed in the processor 10 are input through a bus control logic unit 76. Data to be processed may also come from program input/output control logic unit 77. The bus control logic
60 76 connects storage elements of the random access memory 20 through bus 16 and receives instructions for processing data received from the input/output control 77 or received from the random access memory 20. Thus, the input/output control 77 receives data from the keyboard 14 or the random access memory 20 while the bus control logic 76 receives instructions and/or data from the same memory. Note the different storage sections of the random access memory 20 identifiable for instruction storage and data storage.
65 Device control information from the processor 10 is output through program input/output controller 77

over a data bus 80. Input data on the data bus 80 from the keyboard 14 is processed internally through the processor by instructions on the bus 82 to temporary scratch registers 83. The arithmetic logic unit 73, in response to a control signal on line 72 and in accordance with instructions received on an input/output data bus 80 performs computations and the results can be stored in the temporary scratch registers 83. Various
5 other transfers of data between the arithmetic logic unit 73 and other logic elements of the processor are, of course, possible. Such additional transfers may be to a status register 85, data pointer register 86 or a stack pointer register 87. A program counter 88 is also connected through the data stream bus 82 to various other logic elements in the processor 10.

A particular operating sequence for the processor 10 is determined by instructions and data on the
10 memory bus 16 and input data on the bi-directional bus 80. As an example, in response to received instructions, the processor 10 transfers data stored in the scratch registers 83 to one of the registers 85, 86 or 87. Such operations of processors as detailed in Fig. 2 are considered to be well known and understood by one of ordinary skill in the data processing field. A detailed description of each operation of the processor in Fig. 2 is not deemed necessary for a full understanding of the present invention as claimed.

15 Prior to discussing the flow of the merge control routine and its combination with the text processing system of Fig. 1, an overview of the control system is in order. The specific problem addressed is how to provide an operator interface on a display device that permits merging of documents by either switch codes or named variables in a manner that promotes ease of learning by operators with no programming skills, ease of use and compatibility with existing text processing equipment.

20 The operator creates documents by combining pre-stored text data, paragraphs, or "named variables", which are known as a Shell Document, with pre-sorted personalization information known as a Fill-In Document. The Fill In Document contains one or more Replacement Lists.

The operator has the choice of executing Merge with Switch Codes, as has been done with existing text processing equipment including Magnetic Card equipment, or with Named Variables. The Named Variable
25 allows the operator to mark a position in a document at which "variable" text data is expected to be inserted at a later time. The names of variables (Named Variables) are designated by the operator and may subsequently be used by both the operator and the system for reference. The operator may assign names which relate to the textural information to be inserted (first name or inside address, for example) at the designated position in the document.

30 To execute a Merge operation each Replacement List in the Fill-in Document is merged with the Shell Document. All of the filled-in copies can be stored in a single operator specified output document and optionally printed if desired. Alternatively, the document can be designated to be only printed.

Preparatory to executing a merge operation, there are two documents which must be input by the operator to the Merge application. These documents are created in Create/Revise mode. The two
35 documents are a Shell document and a Fill-In document.

The shell document is a document containing either variables or switch codes at locations corresponding to the places where variable text is to be inserted. Multiple shells can be created within a single document. Each unique shell is identified by a Begin Using Document Format at the top of the first page of the shell.

40 The Fill-In Document contains the Replacement List(s). Replacement Lists can be created by keying each replacement value followed by a switch code if Merge with Switch Codes is to be processed. If the switch code approach is used, no separators are keyed between replacement lists (i.e., there is one list and each replacement value is ended with a switch code). If merge is to be processed with named variables, multiple Replacement Lists are separated within a single document by Page End (PE) codes. If the Named
45 Variable approach is used, replacement values must be entered following the appropriate named variable.

Once the Shell Document and the Fill-In Document have been created, the operator selects Merge Tasks from the Task Selection Menu and the Merge Tasks Menu will be displayed. An illustration of the Merge Tasks Menu as it would appear on the display device is shown in Fig. 3.

A prompt line of the display instructs the operator to type the ID letter to choose an ITEM. The operator
50 makes this selection by typing the appropriate letter in place of the underlined small square at the end of the prompt line of the display and pressing the ENTER key on keyboard 14. The underline represents the position of the cursor and the small square represents the location at which the first keyed character is displayed. For example, to select a Merge with Named Variables, the operator types a "a" in the designated position and presses the ENTER key.

55 In response to the above selection, the Merge with Named Variables Setup Menu is displayed on the display device, and an illustration of this menu is shown in Fig. 4. This menu instructs the operator to make selections concerning the name and location of the Shell Document, the name, location and page numbers to be used for the Fill-In Document and the name and location to be stored for the Merged Document. These selections are made by keying the appropriate ID letter followed by a space and the designated
60 name.

Should the selection be made to Merge with Switch Codes, the Merge with Switch Codes Setup Menu would be displayed and an illustration of this menu is included in Fig. 5. This menu instructs the operator to make choices for the name and location of the Shell Document and the Fill-In Document and the name and location to be stored for the Merged Document. After all the selections are made, the operator presses the
65 ENTER key to start the Merge process.

4

A Hierarchy Diagram of the Merge Subsystem is shown in Fig. 6 which shows the relationship between the various routines used to execute the Merge process called by the application supervisor 90 under the control of the merge supervisor 91.

These routines include the Merge Start/End routines (steps 92, 93) which function to display the Merge Task Selection Menu (step 95) and to set up various components and initiate the Merge process (step 96). The Merge Controller 94 controls the Merge process and the Merge Shell Build 97 deals with the actual process for building and outputting the Shell Document (step 98).

The Shell Document is stored on the designated diskette and a copy of the Shell Document is copied into the Output TSB 26. The Fill-In Document is opened (step 99) and the first page is placed in the Fill-In TSB 26'. Each page includes all the variable information for one document. The pagination routine is then invoked in normal fashion. During this routine, the text in the Output TSB 26 is scanned to detect any control codes. Any control codes such as an INCLUDE instruction, for example, are resolved by the pagination routine by instructing the GET control Block to fetch any designated data for inclusion into the document included in Output TSB or the part of the document stored in Fill-In TSB. The designated data is fetched (steps 103, 104, 109) one record at a time and the fetched data is stored in record buffer 27 and transferred into the Output TSB as needed. The pagination routine then proceeds to resolve the control codes (step 105) as encountered. These control codes may be such codes as the previously mentioned INCLUDE instructions (step 106) or either Switch Codes or Named Variables utilized in the Merge process. In the case of Switch Codes or Named Variables (step 107), the data in the Fill-In TSB is scanned and transferred into the designated insert location (step 108) within the text stored in the Output TSB. The pagination routine continues to merge the designated text data into the Output TSB until a page is completed. At a Page End the TSB Manager 34 stores the completed page on the designated diskette. In addition, if printing is designated by the operator, the page is also sent to the printer 25 (steps 101, 102). The Merge process continues in this manner until all of the pages in the document have been processed (steps 110, 111) Error Handler steps 112 to 115 are also available.

Suitable program routines in program design language (PDL) for implementing the described Merge control system are shown in the following tables:

DESCRIPTIVE—NAME=MERGE START/END

FUNCTION= The Merge Start/End component (MSE- - - - -) contains the routines necessary to load and delete the routines used by the Merge load. In addition, it contains a routine that will display the Merge Task Selection menu and initiate the Merge process.

TABLE 1
MERGE INITIALIZE

```
BEGIN (MSEINIT)
    PUT UP THE 'LOADING TASK' MODE MSG
    LOAD ROUTINES FOR MERGE APPLICATION
    IF LOAD RETURN CODE IS NOT FATAL
        ALLOCATE AND INITIALIZE DATA AREAS
        INITIALIZE POINTER TO DATA AREAS
        INITIALIZE THE SACB FIELDS IN MERGE DATA AREAS
        INITIALIZE DISPLAY STATUS LINE
    ELSE
        PUT UP ERROR MESSAGE
    ENDIF
    RESTORE THE LOADSET RETURN CODE
    RETURN TO CALLER
END (MSEINIT)
```

TABLE 2
MERGE TERMINATION

```
BEGIN (MSETERM)
    DELETE THE MERGE APPLICATION
    FREE THE MERGE DATA AREAS
    RETURN TO CALLER
END (MSETERM)
```

TABLE 3
MERGE SUPERVISOR

```
    BEGIN (MSESUPER)
      FETCH THE KEYBOARD ARRANGEMENT
5     PLACE ARRANGEMENT IN THE MERGE DATA AREA
      ALLOCATE THE MERGE WORKSPACE
      BUILD THE MERGE POOL
      ALLOCATE THE SPACE FOR THE TWO TSBS, THE DOCUMENT
        FORMAT BUFFER, THE VARIABLE FILL-IN PAGE NAME
10    LIST BUFFER, THE MERGE CONTROL BLOCK, AND THE
        GET PAGE(S) CONTROL BLOCK
      CALCULATE AND SAVE THE ADDRESSES OF THE ABOVE DATA AREAS
      UNTIL THE OPERATOR CHOOSES THE "RETURN TO TASK SELECTION" OPTION OR CANCELS THE
      MENU DO
15      IF THE MENU BUFFER DOES NOT EXIST THEN
          ALLOCATE THE MENU BUFFER
          ALLOCATE THE MENU DESCRIPTORS
        ENDIF
        INITIALIZE THE MENU DESCRIPTORS FOR THE MERGE TASK SELECTION MENU
20      DISPLAY THE MERGE TASK SELECTION MENU
        IF OPERATOR DID NOT CANCEL, THEN
          IF THE OPERATOR CHOSE ONE OF THE MERGE DIRECTIVE OPTIONS THEN
            IF SWITCH CODE MERGE WAS CHOSEN THEN
              TURN ON THE APPROPRIATE FLAG
25          ENDIF
            CALL THE MERGE PROCESS CONTROLLER
            IF MERGE COMPLETED SUCCESSFULLY THEN
              DISPLAY "MERGE COMPLETE"
            ELSE
30            IF NO VARIABLES OR SWITCH CODES WERE FOUND THEN
              ENDIF
            ENDIF
          ENDIF
        ENDIF
35    ENDDO
      IF THE MENU BUFFER EXISTS THEN
        FREE THE MENU BUFFER AND THE MENU DESCRIPTORS
      ENDIF
      FREE THE REMAINING DATA AREAS
40    FREE THE MERGE POOL
      FREE THE MERGE WORKSPACE
      RETURN TO CALLER
    END MSESUPER
```

45   DESCRIPTIVE—NAME=MERGE CONTROLLER

FUNCTION= The Merge Controller component (MCN- - - - -) contains the routines which control the Merge
process. This component controls repetitive Letters and Document Assembly functions for
both named VARIABLEs and switch code Merge. This component detects all *setup* errors and
50   redisplays the appropriate setup menu so the operator may correct the error.

55

60

65

TABLE 4
MERGE CONTROLLER

```
BEGIN MCNCNTLR
    INITIALIZE THE SACBS IN THE MAVT
 5  INVOKE MCNSMENU—DISPLAY AND PROCESS THE APPROPRIATE SETUP MENU
    IF MEDIA OUTPUT THEN
        SET UP FOR OUTPUT DOCUMENT
    ENDIF
    IF THE OPERATOR DID NOT ABORT THEN
10      SET THE DEFAULT INCLUDE DISKETTE NAME FIELD IN THE GET CONTROL BLOCK
        DISPLAY THE MERGING MESSAGE ON THE DISPLAY STATUS LINES
        FREE THE MENU DESCRIPTORS AND MENU BUFFER
        WHILE MERGE_NOT_FINISHED —AND— THE ABORT FLAG IS OFF DO
            IF NO TERMINAL ERROR OCCURRED THEN
15          UNTIL A PAGE IS FOUND OR NO MORE PAGES DO
                INVOKE MSBBUMPV—READ THE NEXT VARIABLE
                    LIST INTO THE TSB
                ENDIF
            IF THE MERGE_FINISHED FLAG WAS NOT SET THEN
20              IF NO TERMINAL ERROR OCCURRED THEN
                    INVOKE MSBBLDSH—MERGE THE DOCUMENT
                ENDIF
                IF ANY TERMINAL ERRORS OCCURRED (IN MSBBUMPV OR MSBBLDSH) THEN
                    TURN ON THE ABORT FLAG (TO TERMINATE MERGE) AND CALL
25                      THE ERROR HANDLER SUBROUTINE
                ELSE
                    POLL FOR REQUEST OR END KEYS
                    IF REQUEST WAS HIT THEN
                        PASS CONTROL TO THE REQUEST KEY PROCESSOR
30                      CLEAR THE SCREEN
                    ENDIF
                ENDIF
            ENDIF
        ENDDO
35      INVOKE MSBCOMP—BRING THE MERGE TASK TO AN ORDERLY HALT
    ENDIF
    IF MSBCOMP HAD A TERMINAL ERROR THEN
        CHECK FOR AND HANDLE ANY ERRORS
    ENDIF
40  IF MERGE WAS ABORTED DUE TO ERRORS THEN
        IF PRINT ONLY AND NO PAGES FOUND THEN
            PUT UP NO PAGES FOUND MESSAGE
        ELSE
        DISPLAY THE 'MERGE UNSUCCESSFUL' MESSAGE
45      ENDIF
    ENDIF
    CLEAR THE MERGING MESSAGE ON DISPLAY STATUS LINES
    RETURN TO THE CALLER
END MCNCNTLR
50
```

TABLE 5
SETUP MENU

```
. BEGIN (MCNSETUP)
      OPEN THE SHELL DOCUMENT
5     OPEN THE VARIABLE FILL-IN DOCUMENT
      IF OUTPUT IS NOT 'PRINT ONLY' THEN
        CREATE THE OUTPUT DOCUMENT
      ENDIF
      UNTIL ALL OF DOCUMENT FORMAT IS READ IN DO
10      READ THE NEXT (FIRST) DOCUMENT FORMAT RECORD OF
          THE SHELL DOCUMENT INTO THE DOCUMENT FORMAT BUFFER
        IF OUTPUT IS NOT 'PRINT ONLY' THEN
          WRITE THE DOCUMENT FORMAT RECORD TO THE OUTPUT DOCUMENT
          IF WE ARE WRITING OUT THE FIRST RECORD OF DOCUMENT FORMAT THEN
15          NAME THE RECORD
          ENDIF
        ENDIF
      ENDDO
      IF OUTPUT IS NOT 'PRINT ONLY' THEN
20      WRITE THE DOCUMENT FORMAT RECORD TO THE OUTPUT DOCUMENT
        NAME THE RECORD
      ENDIF
      INITIALIZE THE TWO TSBS AND TSB CONTROL BLOCKS
      HANDLE ANY READ/WRITE ERRORS
25    HANDLE OUTPUT DOCUMENT OPEN ERRORS
      HANDLE VARIABLE DOCUMENT OPEN ERRORS
      HANDLE ANY OPEN ERRORS
      RETURN TO CALLER
    END (MCNSETUP)
30
```

TABLE 6
INITIALIZE MENU

```
     BEGIN (MCNSMENU)
        UNTIL THE MERGE SETUP IS PROPERLY ENTERED
5        —OR— THE OPERATOR CANCELLED WITHOUT CHANGES DO
           IF THIS IS THE FIRST TIME THAT THE MENU WILL
              BE DISPLAYED OR DID THE OPERATOR CANCEL THE
              MENU WITH CHANGES MADE THEN
              INITIALIZE THE NUMERIC MENU DESCRIPTORS
10            FIND THE DEFAULT PAPER FEED TYPE
              DETERMINE WHETHER A DEFAULT DISKETTE EXISTS
                 ON THE SYSTEM AND INITIALIZE THE SHELL
                 DISKETTE MENU DESCRIPTORS
              INITIALIZE THE VARIABLE FILL-IN DISKETTE MENU DESCRIPTORS
15            INITIALIZE THE OUTPUT DISKETTE MENU DESCRIPTORS
              UNLOCK THE SYSTEM RESOURCES
              INITIALIZE THE DOCUMENT MENU DESCRIPTORS
              INITIALIZE THE PAGE NAME LIST MENU DESCRIPTORS .
           ENDIF
20         IF SWITCH CODE MERGE WAS CHOSEN THEN
              POINT TO THE SWITCH CODE MERGE MENU DESCRIPTORS
           ELSE
              POINT TO THE NAMED VARIABLE MERGE MENU DESCRIPTORS
           ENDIF
25         PUT UP THE APPROPRIATE SETUP MENU
           IF THE MENU WAS CANCELLED WITH EITHER CHANGES
              OR NO CHANGES MADE TO THE MENU THEN
              IF THE CANCEL WAS WITH NO CHANGES THEN
                 TURN ON THE ABORT AND CANCEL FLAGS
30            ENDIF
           ELSE
              MARK MENU ITEMS INVALID IF THE OPERATOR DID ·
                 NOT SPECIFY A SHELL DOCUMENT NAME, A SHELL
                 DISKETTE NAME, A VARIABLE FILL-IN DOCUMENT
35               NAME AND A VARIABLE FILL-IN DISKETTE NAME
              IF ALL OF THE REQUIRED PARAMETERS WERE ENTERED THEN
                 PROCESS THE PRINT OUTPUT DOCUMENT OPTION
                 PROCESS THE OUTPUT DOCUMENT NAME OPTION
                 IF THE OPERATOR SPECIFIED AN INVALID OUTPUT TYPE THEN
40               TURN ON THE SETUP ERROR OCCURRED FLAG AND
                    MARK THE APPROPRIATE MENU ITEMS AS INVALID
                 ENDIF
                 IF NO INVALID OUTPUT TYPE ERROR OCCURRED
                 THEN          ·
45                  PROCESS THE CANCEL OR ERROR OPTION
                    PROCESS THE VARIABLE FILL-IN PAGE NAME LIST OPTION
                    INVOKE MCNSETUP—CREATE/OPEN SPECIFIED
                       DOCUMENTS AND INITIALIZE THE SPECIFIED TSBS
                 ENDIF
50            ENDIF
           ENDIF
        ENDDO
        RETURN TO CALLER
     END MCNSMENU
55
```

DESCRIPTIVE—NAME=MERGE SHELL BUILD

FUNCTION= The Merge Shell Build component (MSB- - - - -) deals with the actual process of building and
outputting the shell via the Merge Application. This component is responsible for detecting
and saving all *execution* errors.

TABLE 7
BUILD SHELL

```
   BEGIN (MSBBLDSH)
       IF NOT FIRST TIME THRU THEN
 5     CALL THE GET SHELL ROUTINE TO PUT THE OPERATOR
           SPECIFIED SHELL INTO THE APPROPRIATE OUTPUT DOCUMENT
       ENDIF
       PAGINATE AND RESOLVE THE INCLUDES AND VARIABLES
       RECORD THE LAST PAGE
10     INDICATE END OF SHELL
       CALL PRINTER INTERFACE TO ENTER THE LAST PAGE IN TRAIL PRINT
       RESET END OF SHELL
       IF NO VARIABLE FOUND IN SHELL THEN
           SETUP FOR ABORT
15     ENDIF
       RETURN TO THE CALLER
   END MSBBLDSH
```

TABLE 8
INSERT VALUE INTO OUTPUT

```
20
   BEGIN (MSBINVAL)
       SAVE CHARACTER SET AT END OF VALUE
       MOVE CURSOR TO START OF VALUE
       SAVE CHAR SET AT START OF VALUE
25     RESOLVE ANY CHARACTER SET MISMATCHES AT START OF VALUE
       MOVE CURSOR TO END OF SWITCH CODE OR NAMED VARIABLE
       RESOLVE ANY CHARACTER SET MISMATCHES AT END OF VALUE
       ENDDO
       RETURN TO THE CALLER
30 END (MSBINVAL)
```

TABLE 9
VARIABLE SEARCH

```
   BEGIN (MSBVSRCH)
35     INDICATE A VALUE HAS NOT BEEN FOUND
       INDICATE END OF VALUE NOT FOUND
       IF NOT SWITCH CODE MERGE THEN
           CHECK CURRENT VARIABLE FOR NAME MATCH
           IF VALUE NOT FOUND THEN
40            IF NOT AT TOP OF PAGE THEN
                  PUT REPLACEMENT LIST LOCATION POINTER AT TOP OF PAGE
              ENDIF
              UNTIL VARIABLE NAME MATCH FOUND OR END OF PAGE FOUND DO
                  CHECK CURRENT VARIABLE FOR NAME MATCH
45                IF VARIABLE NAME MATCH NOT FOUND THEN
                      MOVE TO NEXT CONTROL SEQUENCE
                  ENDIF
              ENDDO
           ENDIF
50         IF VALUE FOUND THEN
               SAVE LOCATION OF FIRST CHARACTER
               FIND END OF VALUE
               SAVE LOCATION OF VALUE END
           ENDIF
55     ELSE
           INDICATE A VARIABLE WAS FOUND IN SHELL
           IF NOT AT END OF DOCUMENT THEN
               INDICATE VALUE FOUND
               SAVE LOCATION OF VALUE START
60             MOVE TO NEXT SWITCH CODE OR END OF DOCUMENT
               SAVE LOCATION OF END OF VALUE
           ENDIF
       ENDIF
       RETURN TO CALLER
65 END MSBVSRCH
```

TABLE 10
SHELL BUILD COMPLETION

```
    BEGIN (MSBCOMP)
       REINITALIZE MERGE CONTROL BLOCK
 5     REINITIATE GET CONTROL BLOCK
       CLOSE THE FILL-IN DOCUMENT
       CLOSE THE SHELL DOCUMENT
       CLOSE THE OUTPUT DOCUMENT
       COMPLETE PRINTING OF OUTPUT BACKGROUND
10     RETURN TO CALLER
    END MSBCOMP
```

TABLE 11
RESOLVE INCLUDES

```
15  BEGIN (MSBRSINC)
       SETUP TO RESOLVE INCLUDED PAGES
       RESOLVE INCLUDES BY FETCHING PAGE
       HANDLE ERRORS
       IF ABORT INDICATED THEN
20        INDICATE IT IN RETURN CODE
       ENDIF
       RETURN TO CALLER
    END (MSBRSINC)

25



30



35



40



45



50



55



60



65
```

TABLE 12
RESOLVE PAGE

```
      BEGIN (MSBRSPG)
        IF NOT END OF MERGE THEN
  5       IF PRINT OUTPUT THEN
            IF PRINT ONLY THEN
              IF $SYSDOC1 PRINTING AND PROCESSING
              THEN GIVE PAGE TO PRINTER
            ELSE
 10           IF $SYSDOC2 IS PRINTING AND PROCESSING THEN
                GIVE PAGE TO PRINTER
              ELSE
                IF ONE DOCUMENT PRINTING AND THE OTHER
                PROCESSING THEN
 15               IF END OF A SHELL THEN
                    DETERMINE DOCUMENT STATUS
                    IF SYSTEM DOCUMENT IN THE QUEUE IS NOT PRINTING THEN
                      POST MERGE WAITING UNTIL DOCUMENT NOW PRINTING IS FINISHED
                      UNTIL SYSTEM DOCUMENT FINISHED
 20                     PRINTING OR END PRESSED DO .
                        POLL FOR REQUEST KEY
                        POLL FOR END KEY
                      ENDDO
                      TAKE MESSAGE DOWN
 25                 ENDIF
                  ENDIF
                  DETERMINE DOCUMENT STATUS
                  IF DOCUMENT THRU PRINTING THEN
                  IF NOT AN ABORT THEN
 30               ENDIF
                    GIVE NEW DOCUMENT TO PRINTER
                    INDICATE DOCUMENT IS PRINTING
                  ENDIF
                ELSE
 35               IF $SYSDOC1 PROCESSING AND $SYSDOC2
                    NONEXISTENT THEN
                    GIVE NEW DOCUMENT TO PRINTER
                    IF DOCUMENT SUBMITTED TO PRINT THEN
                    INDICATE DOCUMENT IS PRINTING
 40               ENDIF
                  ENDIF
                ENDIF
              ENDIF
            ENDIF
 45       ELSE
            GIVE PAGE TO TRAIL PRINT
            INDICATE DOCUMENT IS PRINTING
          ENDIF
          SAVE CURRENT PAGE NAME OF OUTPUT DOCUMENT
 50       ENDIF
        ELSE
          POLL FOR REQUEST KEY
          POLL FOR END KEY
        ENDIF
 55     RETURN TO THE CALLER
      END MSBRSPG
      $SYSDOC1 AND $SYSDOC2 ARE TEMPORARY SYSTEM DOCUMENTS


 60



 65
```

TABLE 13
GET NEXT REPLACEMENT LIST

```
    BEGIN (MSBBUMPV)
      IF NOT SWITCH CODE MERGE THEN
 5      UNTIL NEXT LIST FOUND OR NO MORE LISTS DO
          IF ALL REPLACEMENT LISTS ARE TO BE USED AND
            IF FIRST TIME THEN
            GET FIRST PAGE
          ELSE
10          IF ALL REPLACEMENT LISTS ARE TO BE USED THEN
              SAVE NEXT PAGE NAME OF REPL. LIST
            ELSE
            IF FIRST TIME THRU THEN
            INDICATE DONE ONCE
15          ENDIF
              SAVE NEXT PAGE NAME OF REPL. LIST
            ENDIF
            IF NOT ON LAST PAGE OF DOCUMENT OR NOT ON
            LAST PAGE OF PAGE LIST THEN
20            GET THE NEXT PAGE
            ENDIF
          ENDIF
        ENDDO
      ELSE
25      IF FIRST TIME THRU THEN
          GET THE FIRST PAGE
        ELSE
          IF END OF DOCUMENT THEN
          INDICATE MERGE COMPLETE
30        ELSE
            IF NEXT CHARACTER IS A LINE END THEN
              MAKE SURE ANOTHER VARIABLE EXISTS
            ENDIF
          ENDIF
35      ENDIF
      ENDIF
      IF NOT FINISHED MERGING THEN
        INDICATE PAGE FOUND
        UPDATE THE PAGE NAME
40    ENDIF
      ERROR HANDLING
      RETURN TO CALLER
    END MSBBUMPV

45




50




55




60




65
```

TABLE 14
GET INTERMEDIATE SHELL

```
    BEGIN (MSBGISHL)
       IF PRINT ONLY OUTPUT THEN
5        IF FIRST TIME THRU THEN
            OPEN (CREATE) $SYSDOC1
            SET $SYSDOC1 STATUS TO PROCESSING
         ENDIF
         IF $SYSDOC1 STATUS IS PRINTING THEN
10         RESET $SYSDOC1 PROCESSING
           DELETE $SYSDOC2
           OPEN (CREATE) $SYSDOC2
           SET $SYSDOC2 STATUS TO PROCESSING
         ELSE
15         IF $SYSDOC2 STATUS IS PRINTING THEN
             RESET $SYSDOC2 PROCESSING
             DELETE $SYSDOC1
             SET $SYSDOC1 STATUS TO PROCESSING
           ENDIF
20       ENDIF
         ESTABLISH TSB SESSION WITH ACTIVE DOCUMENT
         COPY DOCUMENT FORMAT FROM BUFFER TO ACTIVE DOCUMENT
       ENDIF
       IF PRINT ONLY OR IF FIRST TIME THRU AND MEDIA OUTPUT THEN
25       FETCH AND STORE DOCUMENT FORMAT
         SETUP TO READ AND STORE DOCUMENT FORMAT
         READ DOCUMENT FORMAT
         STORE DOCUMENT FORMAT
       ENDIF
30     STORE STARTING PAGE NAME
       MOVE OPERATOR SPECIFIED SHELL INTO APPROPRIATE OUTPUT DOCUMENT
       RETURN TO THE CALLER
    END MSBGISHL
```

                    DESCRIPTIVE-NAME=MERGE ERRORS
35
FUNCTION= The Merge Errors component (MER- - - - -) deals with the insertion of the output shell error
          messages and the quantitative error message at the end of the shell in which the error(s)
          occurred.

TABLE 15
MERGE EXECUTION ERROR HANDLER

```
40
    BEGIN (MERHNDLR)
       GET ADDRESS OF MERGE ERROR CONTROL BLOCK
       GET TSB CONTROL BLOCK ADDRESS
       GET THE ERROR NUMBER
45     INDICATE AN EXECUTION ERROR FOUND DURING MERGE
       SAVE CURRENT TSB LOCATION
       BUMP THE SEQUENTIAL ERROR NUMBER
       DETERMINE WHICH MESSAGE TO USE FROM ERROR MESSAGE TABLE
       GET START OF TABLE
50     SUBTRACT ONE FROM ERROR CODE TO GET CORRECT DISPLACEMENT INTO TABLE
       FIND OFFSET OF MESSAGE DISPLACEMENT
       SAVE THE MESSAGE NUMBER
       GENERATE POINTER TO WORK AREA FOR BUILDING THE ERROR MESSAGE
       ESTABLISH TSB ADDRESSABILITY
55     SAVE THE POINTER
       BUILD MESSAGE
       MOVE MESSAGE INTO TSB
       ESTABLISH TSB ADDRESSABILITY
       CALCULATE HOW MANY CHARACTERS TO MOVE
60     MOVE MESSAGE INTO TSB
       IF CANCEL ON ERROR IS ACTIVE THEN
         INDICATE ABORT
       ENDIF
       RETURN TO THE CALLER
65  END MERHNDLR
```

TABLE 16
MERGE ERROR MESSAGE NUMBER TABLE
BEGIN (MERTBL)
END MERHNDLR
5 THIS TABLE CONTAINS A LIST OF ALL THE MERGE EXECUTION ERRORS

While the invention has been particularly shown and described with reference to a preferred embodiment it will be understood by those skilled in the art that various other changes by equivalent means may be made such as utilizing other types of input/output devices, other types of displays other memory organizations
10 without departing from the scope of the invention as defined by the claims.

Claims

1. Interactive text processing system in which a document input by way of a keyboard (14) is stored
15 (20), displayed (22) to an operator, and merged with other keyed data in accordance with directions supplied to said system by an operator interacting with the keyboard (14) and the display unit, comprising:
means (90, 91) allowing the operator to signal by way of the keyboard, by a first or a second control code, the location in a document at which an insert of pre-stored text data is to be added to the document;
means (94) causing the system to display a first menu (fig. 3) of predetermined task selections
20 selectable by the operator,
means allowing the operator to select by way of the keyboard either a first type (a, fig. 3) of merge operation operable in response to said first control code or a second type (b, fig. 3) of merge operation operable in response to said second control code,
means causing the system to display, when said first type of merge operation is selected by the
25 operator, a second menu of predetermined task selections or, when said second type of merge operation is selected by the operator, a third menu of predetermined task selections,
means allowing the operator to specify the way of the keyboard and identification of an insert of pre-stored text data, and
means (44) for causing the system to fetch, in response to the specified identification, the appropriate
30 insert of pre-stored text data and to merge said data into said document at the signalled location to produce a revised document.
2. Interactive text processing system according to claim 1 characterized in that said first control code comprises conventional coded data known as Switch Codes.
3. Interactive text processing system according to claim 1 characterized in that first control code
35 comprises operator's set up references related to the textual information to be inserted and designated as "Names variables".
4. A method of operating an interactive text processing system in which a document input by way of a keyboard (14) is stored (20), displayed (22) to an operator, and merged with other keyed data in accordance with directions supplied to said system by an operator interacting with the keyboard and the display unit,
40 the method comprising the steps of:
allowing the operator to signal by way of the keyboard, by a first or a second control code, the location in a document at which an insert of pre-stored text data is to be added to the document;
causing the system to display a first menu of predetermined task selections selectable by the operator,
allowing the operator to select by way of the keyboard either a first type of merge operation operable in
45 response to said first control code or a second type of merge operation operable in response to said second control code,
causing the system to display, when said first type of merge operation is selected by the operator, a second menu of predetermined task selections or, when said second type of merge operation is selected by the operator, a third menu of predetermined task selections,
50 allowing the operator to specify by way of the keyboard the identification of an insert of pre-stored text data, and
causing the system to fetch, in response to the specified identification, the appropriate insert of pre-stored text data and to merge said data into said document at the signalled location to produce a revised document.
55 5. Method according to claim 4, characterised in that said first control code comprises Switch Codes.
6. Method according to claim 4 characterized in that said second control code comprises Named Variables.

Patentansprüche

60
1. Interaktives Textverarbeitungssystem, in dem ein über eine Tastatur (14) eingegebenes Dokument (20) gespeichert, einem Bediener angezeigt (22) mit anderen über eine Tastatur angegebene Daten gemäss Anweisungen verschmolzen wird, die dem besagten System durch einen Bediener mit Hilfe der Tastatur (14) und der Anzeigeeinheit mitgeteilt werden, enthaltend:
65 Mittel (90, 91), die es dem Bediener gestatten, über die Tastatur durch einen ersten oder einen zweiten

Steuercode die Stelle in einem Dokument anzugeben, in dem vorgespeicherte Textdaten in das Dokument eingefügt werden sollen.

Mittel (94), die das System veranlassen, ein erstes Menu (Abb. 3) vorgegebener Aufgaben anzuzeigen, die vom Bediener gewählt werden können.

5   Mittel, die es dem Bediener gestatten, über die Tastatur entweder einen ersten Typ (a, Abb. 3) eines Veschmelzungsvorgangs vorzunehmen, der sich in Antwort auf den besagten ersten Steuercode durchführen lässt, oder von einem zweiten Typ, der sich als Antwort auf den zweiten Steuercode durchführen lässt.

Mittel, welche das System veranlassen, wenn besagter erster Verschmelzungstyp vom Bediener
10 gewählt wird, ein zweites Menü vorgegebener Aufgabe anzuzeigen, oder wenn der zweite Typ der Verschmelzungsvorgänge gewählt wird, ein drittes Menü mit vorgegebenen Aufgaben.

Mittel, die es dem Bediener gestatten, über die Tastatur die Identifizierung einer Einfügung von vorgespeicherten Textdaten vorzunehmen, und

Mittel (44), welche das System veranlassen, andsprechend auf die spezifizierte Identifizierung die
15 entsprechende Einfügung vorgespeicherter Textdaten vorzunehmen und die besagten Daten in besagtem Dokument an der angegebenen Stelle einzufügen, um ein überarbeitetes Dokument zu erstellen.

2. Interaktives Textverarbeitungssystem gemäss Anspruch 1, dadurch gekennzeichnet, dass der erste Kontrollkode konventionell kodierte Daten enthält, die als Umschaltkode bekannt sind.

3. Interaktives Testverarbeitungssystem gemäss Anspruch 1, dadurch gekennzeichnet, dass der erste
20 Steuercode vom Bediener eingesetzte Referenzen enthält, die sich auf die einzufügende Textinformation beziehen und also "Variablennamen" bezeichnet sind.

4. Methode der Betätigung eines interaktiven Textverarbeitungssystem, in dem ein über eine Tastatur eingegebenes Dokument (14) gespeichert (20), dem Bediener angezeigt (22) und mit anderen verschlüsselten Daten gemäss den dem System vom Bediener über Tastatur und Anzeigeeinheit erteilten
25 Weisungen verschmolzen wird, wobei die Methode folgende Schritte enthält:

dem Bediener wird ermöglicht, über die Tastatur durch einen ersten oder zweiten Steuercode die Stelle in einem Dokument anzugeben, an der eine Einfügung vorgespeicherter Textdaten im Dokument vorgenommen werden soll,

das System wird veranlasst, ein erstes Menü vorgegebener Aufgaben anzuzeigen, aus denen der
30 Bediener eine auswählen kann;

dem Bediener wird gestattet, über die Tastatur entweder einen ersten Typ eines Vermischungs- vorgangs auszuwählen, der sich in Antwort auf besagten ersten Steuercode durchführen lässt, oder einen zweiten Typ Vermischungsvorgang, der in Antwort auf besagten zweiten Steuercode ausgeführt wird,

das System wird veranlasst, wenn besagter erster Verschmelzungstyp vom Bediener gewählt wird, ein
35 zweites Menü mit vorgegebenen Aufgaben anzuzeigen, oder wenn besagter zweiter Typ des Verschmelzungsvorgangs vom Bediener gewählt wird, ein drittes Menü vorgegebener Aufgaben,

dem Bediener wird gestattet, über die Tastatur die Identifizierung der Einfügung vorgespeicherter Textdaten zu spezifizieren,

das System wird veranlasst, ansprechend auf die spezifierte Identifikation die gewünschten
40 vorgespeicherten Textdaten zu holen und besagte Daten in das besagte Dokument an der angegebenen Stelle einzufügen, um ein überarbeitetes Dokument herzustellen.

5. Verfahren gemäss Anspruch 4, dadurch gekennzeichnet, dass besagte erste Kontrolle Umschaltcodes enthält.

6. Methode gemäss Anspruch 4, dadurch gekennzeichnet, dass besagte zweite Steuerkode benannte
45 Variablen enthält.

Revendications

50   1. Système de traitement de texte interactif dans lequel une entrée de document effectuée au moyen d'un clavier (14) est mise en mémoire (20), affichée en (22) pour l'opérateur et mélangée à d'autres données entrées au clavier selon des directions délivrées audit système par l'opérateur en interaction avec le clavier (14) et l'unité d'affichage, comprenant:

des moyens (90, 91) permettant à l'opérateur de signaler au moyen du clavier et par un premier ou un
55 second code de commande, l'emplacement dans un document où des données de texte pré- ammagasinées doivent être ajoutées par insertion,

des moyens (94) provoquant l'affichage par le système d'un premier menu (Figure 3) d'une sélection de tâches prédéterminées pouvant être sélectionnées par l'opérateur,

des moyens permettant à l'opérateur de sélectionner au moyen du clavier soit un premier type (a,
60 Figure 3) d'opération de fusion pouvant être effectuée en réponse audit premier code de commande, soit un second type (b, Figure 3) d'opération de fusion pouvant être effectuée en réponse audit second code de commande,

des moyens provoquant l'affichage par le système lorsque ledit premier type d'opération de fusion est choisi par l'opérateur, d'un second menu de tâches prédéterminées ou, lorsque ledit second type
65 d'opération de fusion est choisi par l'opérateur, d'un troisième menu de tâches prédéterminées,

16

0 075 732

des moyens permettant à l'opérateur de spécifier au moyen du clavier, l'identification d'une insertion de données de texte pré-emmagasinées, et

des moyens (44) pour provoquer le retrait par le système, en réponse à l'identification spécifiée, de l'insertion appropriée de données de texte pré-emmagasinées et la fusion desdites données dans ledit
5 document à l'emplacement signalé pour obtenir un document révisé.

2. Système de traitement de texte interactif selon la revendication 1 caractérisé en ce que ledit premier code de commande comprend des données codées classiques appelées "Codes de Commutation".

3. Système de traitement de texte interactif selon la revendication 1 caractérisé en ce que le premier code de commande comprend des références de mise en place de l'opérateur relatives à l'information textuelle à insérer et appelées "Variables nommées".

4. Une méthode d'actionnement d'un système de traitement de texte interactif dans lequel une entrée de document au moyen d'un clavier (14) est mise en mémoire (20), affichée en (22) pour un opérateur et mélangée avec d'autres données entrées au clavier selon des revendications délivrées audit système par un opérateur en interaction avec le clavier et l'unité d'affichage, la méthode:
15 permettant à l'opérateur de signaler par l'intermédiaire du clavier, au moyen d'un premier ou d'un seconde code de commande, l'emplacement dans un document où des données de texte pré-emmagasinées doivent être ajoutées,

provoquant l'affichage par le système d'un premier menu de tâches prédéterminées pouvant être choisies par l'opérateur.
20 permettant à l'opérateur de sélectionner au moyen du clavier soit un premier type d'opération de fusion pouvant être actionné en réponse audit premier code de commande, soit un second type d'opération de fusion pouvant être actionnée en réponse audit seconde code de commande,

provoquant l'affichage par le système lorsque ledit premier type d'opération de fusion est choisi par l'opérateur, d'un second menu de tâches prédéterminées ou lorsque ledit second type d'opération de
25 fusion est choisi par l'opérateur, d'un troisième menu de tâches prédéterminées,

permettant à l'opérateur de spécifier au moyen du clavier, l'identification d'une insertion de données de texte pré-emmagasinées, et

provoquant le retrait par le système, en réponse à l'identification spécifiée, de l'insertion appropriée de données de texte pré-emmagasinées et la fusion desdites données dans ledit document à l'emplacement
30 signalé pour obtenir un document révisé.

5. Méthode selon la revendication 4 caractérisée en ce que ledit premier code de commande comprend des "Codes de Commutation".

6. Méthode selon la revendication 4 caractérisée en ce que ledit seconde code de commande comprend des "Variables nommées".

35

40

45

50

55

60

65

FIG. 1

FIG. 2

```
DSK001 |                                              |          |Kyb  |    |

                         MERGE TASKS


         ID    ITEM

         a     Merge with Named Variables

         b     Merge with Switch Codes

         c     Go to Task Selection
```

When finished with this menu, press ENTER.

Type ID letter to choose ITEM; press ENTER:

FIG. 3

```
Merging Variables  |                                          |        |
DSK001 |           |          |              |            |Kyb |    |

              MERGE WITH NAMED VARIABLES SETUP

                            YOUR      POSSIBLE
                            CHOICE    CHOICES

ID   ITEM

a    Shell Document Name
b    Diskette Name

c    Fill-In Document Name
d    Diskette Name
e    System Page Number (s)

f    Merged Document Name
g    Diskette Name

h    Print Merged Document     1       1 = Yes      2 = No
i    Cancel On Error           1       1 = Yes      2 = No
j    Paper Handling            2       1 = Cut Paper, Manual Feed
                                       2 = Cut Paper, Automatic Fee
                                       3 = Continuous Paper

When finished with this menu, press ENTER.
Type ID letter to choose ITEM; press ENTER:
```

FIG. 4

4

Merging Variables
DSK001 |Kyb |

MERGE WITH SWITCH CODES SETUP

| | | YOUR | POSSIBLE |
ID	ITEM	CHOICE	CHOICES
a	Shell Document Name		
b	Diskette Name		
c	Fill-In Document Name		
d	Diskette Name		
e	Merged Document Name		
f	Diskette Name		
g	Print Merged Document	1	1 = Yes 2 = No
h	Cancel On Error	1	1 = Yes 2 = No
i	Paper Handling	2	1 = Cut Paper, Manual Feed
			2 = Cut Paper, Automatic Feed
			3 = Continuous Paper

When finished with this menu, press ENTER.

Type ID letter to choose ITEM; press ENTER:

FIG. 5

FIG. 6

```
*************************
*NOTE:  SECTIONS MARKED*
*WITH '*' ARE NOT IN   *
*THE MERGE SUBSYSTEM   *
*************************
```